

# Ithaca Visby



## GENERAL

<b>Name</b>	Ithaca Visby
<b>Type</b>	Handysize Bestway
<b>Built</b>	April 2010
<b>Flag</b>	Isle of Man
<b>Class</b>	American Bureau of Shipping
<b>DWAT</b>	35.083 mts on 10,80 m (summer)
<b>TPC</b>	46,55 mts/cm (summer)
<b>Tonnage</b>	22.409 (GT) / 12.013 (NT)
<b>LOA</b>	179,90 m
<b>Beam</b>	28,40 m
<b>Depth</b>	15,00 m

## HOLDS & HATCHES

**Hatchcover type** TTS hydraulic transfolding hatch covers  
**Tanktop strength** 20 mt/sqm

		<u>Length</u>	<u>Breadth (fore/aft)</u>	<u>Height</u>	<u>Grain (cbm)</u>	<u>Bale (cbm)</u>
<b>Hatchcovers</b>	<b>No.1</b>	14,40 m	17,60 m			
	<b>No.2</b>	20,00 m	19,20 m			
	<b>No.3</b>	20,00 m	19,20 m			
	<b>No.4</b>	20,00 m	19,20 m			
	<b>No.5</b>	20,00 m	19,20 m			
<b>Cargo holds</b>	<b>No.1</b>	25,60 m	9,60 m	24,50 m	6.918,90	6.598,13
	<b>No.2</b>	28,60 m	24,50 m	24,50 m	10.001,30	9.665,95
	<b>No.3</b>	27,20 m	24,50 m	24,50 m	9.382,70	9.045,69
	<b>No.4</b>	28,60 m	24,50 m	24,50 m	9.994,00	9.665,95
	<b>No.5</b>	24,80 m	24,50 m	11.20 m	7.975,50	7.611,12
<b>Total Capacity</b>					44.272,40	42.586,84

## GEAR & ENGINE

<b>Crane type</b>	Electro-hydraulic cranes – not combinable
<b>SWL</b>	4 x 30.5 mt each
<b>Outreach</b>	Max. 24,0 m
<b>Grabs type</b>	No
<b>Capacity</b>	N/A
<b>Main Engine type</b>	MAN B&W 6S50MC-C
<b>Output</b>	7600 KW
<b>Aux. Engine type</b>	STX MAN B&W 5L23/30H
<b>Output</b>	3 x 650 KW

## OTHER FITTINGS

<b>Logs fitted</b>	Yes
<b>Cement holes</b>	2 x 700 mm diameter per hold
<b>Ventilation</b>	Electrical
<b>Grain fitted</b>	Yes
<b>CO2 fitted</b>	Yes
<b>A60 bulkhead</b>	Yes
<b>Australian hold ladder</b>	Yes
<b>Strengthened for heavy cargo</b>	Yes