

Ithaca Riga



GENERAL

Name	Ithaca Riga
Type	Handysize Bestway
Built	November 2010
Flag	Isle of Man
Class	American Bureau of Shipping
DWAT	35.052,0 mts on 10,80 m (summer)
TPC	46,55 mts/cm (summer)
Tonnage	22.409 (GT) / 12.013 (NT)
LOA	179,90 m
Beam	28,40 m
Depth	15,00 m

HOLDS & HATCHES

Hatchcover type	TTS hydraulic transfolding hatch covers
Tanktop strength	20 mt/sqm

		<u>Length</u>	<u>Breadth (fore/aft)</u>	<u>Height</u>	<u>Grain (cbm)</u>	<u>Bale (cbm)</u>
Hatchcovers	No.1	14,40 m	17,60 m			
	No.2	20,00 m	19,20 m			
	No.3	20,00 m	19,20 m			
	No.4	20,00 m	19,20 m			
	No.5	18,40 m	19,20 m			
Cargo holds	No.1	25,60 m	9,60 m	24,50 m	6.918,90	6.598,13
	No.2	28,60 m	24,50 m	24,50 m	10.001,30	9.665,95
	No.3	27,20 m	24,50 m	24,50 m	9.382,70	9.045,69
	No.4	28,60 m	24,50 m	24,50 m	9.994,00	9.665,95
	No.5	24,80 m	24,50 m	11.20 m	7.975,50	7.611,12
Total Capacity					44.272,40	42.586,84

GEAR & ENGINE

Crane type	Electro-hydraulic cranes – not combinable
SWL	4 x 30.5 mt each
Outreach	Max. 24,0 m
Grabs type	No
Capacity	N/A
Main Engine type	MAN B&W 6S50MC-C
Output	7600 KW
Aux. Engine type	STX MAN B&W 5L23/30H
Output	3 x 650 KW

OTHER FITTINGS

Logs fitted	Yes
Cement holes	2 x 700 mm diameter per hold
Ventilation	Electrical
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	Yes