

# Ithaca Patience



© Nils Junge  
MarineTraffic.com

## GENERAL

Name	Ithaca Patience
Type	Bulk Carrier / Logger
Built	March 2010
Flag	Panama
Class	NKK
DWAT	28.349 mts on 9,80 m (summer)
TPC	39,6 mts/cm (summer)
Tonnage	17.018 (GT) / 10.108 (NT)
LOA	163,37 m
Beam	27,20 m
Depth	13,60 m

## HOLDS & HATCHES

Hatchcover type	Electric-Hydraulic folding type weathertight hatch covers
Tanktop strength	1&3 16,92 t/m <sup>2</sup> 2&4 15,00 t/m <sup>2</sup> 5 17,03 t/m <sup>2</sup>

		<u>Length</u>	<u>Breadth (fore/aft)</u>	<u>Height</u>	<u>Grain (cbm)</u>	<u>Bale (cbm)</u>
Hatchcovers	No.1	13,60 m	16,00 m			
	No.2	19,20 m	17,60 m			
	No.3	19,20 m	17,60 m			
	No.4	19,20 m	17,60 m			
	No.5	19,20 m	17,60 m			
Cargo holds	No.1	19,00 m	23,20 m	24,50 m	5.314,00	5.019,52
	No.2	20,80 m	26,20 m	24,50 m	8.148,22	7.831,74
	No.3	20,80 m	26,20 m	24,50 m	8.199,58	7.882,20
	No.4	20,80 m	26,20 m	24,50 m	8.223,83	7.882,20
	No.5	20,80 m	27,20 m	11.20 m	7.435,00	7.127,17
Total Capacity					37.320,63	35.742.83

## GEAR & ENGINE

Crane type	Electro-hydraulic cranes – not combinable
SWL	4 x 30.5 mt each
Outreach	Max. 10,40 m
Grabs type	No
Capacity	N/A
Main Engine type	Makita-Mitsui MAN B&W 6S42MC
Output	6150 KW
Aux. Engine type	Yanmar 6ECOI 18AL
Output	3 x 450 KW

## OTHER FITTINGS

Logs fitted	Yes
Cement holes	1 each portside, diameter 700 mm
Ventilation	Natural
Grain fitted	Yes
CO2 fitted	No
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	No